

Automatic Side-Seal Strapping

The SQ-800Y with brushless DC Motor is a side-seal mode SQ-800 such as self-loading, refeed and loop ejection.



advanced features of the

- Wide Adaptability to Fully-Automated Packaging Line**

The machine fits any existing or proposed conveyor system, adapts to any conveyor height and requires no special equipment.

Several options are available to make it easy to integrate the SQ-800Y into a conveyor system. Larger arch sizes offer a wide range of applications, particularly for large and heavy packages.

- Strapping Speed**

Standard strapping rate is 50 straps/min, even when tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.



SQ-800Y

Standard Specifications (Arch size 600 mm wide x 850 mm high)

Dimension	Width	1500 mm
	Height	1723 mm
	Depth	610 mm
	Weight	180 kg
Package Size	Max	W 580 X H 820 mm
	Min	W 30 X H 80 mm
Joint / Strap		heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm
Strap Tension		784 N (80 kgf) / 450 N (46 kgf) *CE Spec.
Power Supply		110, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



บริษัท นานดีอินเตอร์เทรด จำกัด
NANDEE INTER-TRADE CO., LTD.

314,316,318,320,322 ซอยจันทน์ 32 ถนนจันทน์ แขวงทุ่งวัดดอน เขตสาทร กทม. 10120

☎ : 0-2675-8239
 LINE : @nandeeintertrade
 f : nandeeintertrade
 🌐 : www.nandee.co.th
 ✉ : marketing@nandee.co.th
 sales@nandee.co.th